CONTENTS

| Subj | ect: | Page No. |
|------------------------------------|--|-------------|
| Title page | | |
| Title page Certificate of approval | | |
| Certificate Certificate | | |
| Declaration | | |
| Acknowledgement | | iv v |
| | of symbols | vi |
| | of abbreviations | X |
| Abst | | xi |
| Cont | | xiii |
| Cha | pter 1: Introduction | |
| 1.1 | General Background | 1 |
| 1.2 | | 3 |
| 1.3 | Lay out of the Work | 4 |
| Chaj | pter 2: Literature Survey | |
| 2.1 | Historical background of dual-phase steel | 7 |
| 2.2 | Metallurgy of dual-phase steel | 9 |
| | 2.2.1 Ferrite-martensite dual phase steel | 11 |
| | 2.2.1.1 Heat Treatment | 11 |
| | 2.2.1.2 Microstructure | 13 |
| | 2.2.1.3 Effect of composition | 13 |
| | 2.2.2 Ferrite-bainite dual-phase steel | 15 |
| 2.3 | Bainitic Transformation | 16 |
| 2.4 | Mechanical properties of dual-phase steel | 17 |
| | 2.4.1 Strength | 17 |
| | 2.4.2 Ductility | 20 |
| | 2.4.3 Deformation behaviour | 22 |
| 2.5 | Fatigue behavior | 24 |
| | 2.5.1 Short crack: definition and significance | 26 |
| | 2.5.2 Measurement of short crack growth | 32 |
| | 2.5.3 Fatigue crack closure | 34 |
| | 2.5.4 Long crack fatigue threshold | 36 |
| | 2.5.5 Measurement of long crack growth | 36 |
| | 2.5.6 Factors affecting fatigue thresholds | 38 |
| | 2.5.7 Factors affecting fatigue crack propagation | 39 |
| 2.6 | Appraisal of the problem | 43 |
| | pter 3: Development of ferrite-bainite dual-phase steels | |
| 3.1 | Introduction | 45 |
| 3.2 | Experimental procedure | 45 |
| | 3.2.1 Steels and their chemical compositions | 46 |
| | 3.2.2 Heat treatments | 46 |
| | 3.2.3 Inclusion characterization | 47 |
| | 3.2.4 Metallographic examinations | 48 |
| | 3.2.4.1 Preparation and examination of microstructures | 48 |
| | 3.2.4.2 Volume fraction of ferrite and bainite | 49 |
| | 3.2.4.3 Grain size measurement | 50 |
| | 3.2.4.4. Estimation of ratained austanite | 50 |

| | 3.2.4.5 Hardness measurement | 51 |
|------------|--|-----|
| 3.3 | Results and discussion | 51 |
| | 3.3.1 Cleanliness of steels | 52 |
| | 3.3.2 TTT diagram and heat treatment of steel | 55 |
| | 3.3.3 Microstructure | 60 |
| | 3.3.4 Phase-characterization by macro and microhardness | 68 |
| 3.4 | Summary | 72 |
| Cha | pter 4: Tensile behaviour of ferrite-bainite dual-phase steels | |
| 4.1 | Introduction | 73 |
| 4.2 | Experimental procedure | 74 |
| | 4.2.1 Specimen preparation | 74 |
| | 4.2.2 Tensile testing | 75 |
| | 4.2.3 SEM Examinations of tensile fracture surfaces | 75 |
| 4.3 | Results and discussions | 76 |
| | 4.3.1 General | 76 |
| | 4.3.2 Role of bainite/martensite on strength | 79 |
| | 4.3.2.1 Tensile strength | 79 |
| | 4.3.2.2 Yield strength | 85 |
| | 4.3.3 Role of bainite/martensite on ductility | 86 |
| | 4.3.4 Role of bainite/martensite on work hardening behaviour | 90 |
| | 4.3.4.1 Strain hardening behaviour: Hollomon analysis | 90 |
| | 4.3.4.2 Analysis using Crussard-Jaoul approach | 96 |
| | 4.3.5 Fractographic studies of tensile fractured surfaces | 99 |
| 4.4 | Conclusions | 101 |
| | pter 5: Fatigue threshold of ferrite-bainite steels | |
| 5.1 | Introduction | 103 |
| 5.2 | Experimental procedure | 104 |
| | 5.2.1 Design of specimen | 105 |
| <i>-</i> 0 | 5.2.2 Test details | 106 |
| 5.3 | Results and discussions | 108 |
| | 5.3.1 Pre-cracking of specimens | 110 |
| | 5.3.2 Estimation of fatigue threshold | 113 |
| | 5.3.2.1 Methods of threshold measurement | 117 |
| | 5.3.2.2 The rate of load shedding | 120 |
| | 5.3.2.3 The definition of fatigue threshold | 122 |
| | 5.3.2.4 Scatter of the estimation of fatigue threshold values | |
| | 5.3.3 Comparative assessment of estimated fatigue thresholds | 125 |
| <i>5</i> 1 | 5.3.4 Effect of microstructure | 129 |
| 5.4 | Conclusions | 137 |
| | pter 6: Studies on short fatigue crack growth behaviour Introduction | 120 |
| 6.1 | | 139 |
| 6.2 | Experimental procedure | 140 |
| 6.2 | 6.2.1 Short crack growth testing | 141 |
| 6.3 | Short fatigue crack growth behaviour in S1-steel | 142 |
| | 6.3.1 Crack initiation studies related to short crack | 142 |
| | 6.3.2 Variation of crack length with number of cycles | 144 |
| | 6.3.3 Variation of crack growth rate with the crack length | 146 |
| | 6.3.4 Variation of crack growth rate with stress intensity factor | 150 |
| | range 6.3.5 Near long crack fatigue thresholds | 153 |
| | U.J.J INCAL TOING CLACK LAUGUE UHESHOIUS | 133 |

| | 6.3.6 Effect of microstructure on short crack growth behaviour | 156 | |
|--|--|-----|--|
| 6.4 | Short fatigue crack growth behaviour in S2-steel | 158 | |
| 6.5 | Short fatigue crack growth behaviour in S3-steel | 162 | |
| 6.6 | Conclusions | 164 | |
| Chapter 7: Concluding remarks and scope for further research | | | |
| | Concluding remarks and scope for further research | 167 | |
| References | | 173 | |
| Curriculum Vitae | | | |