

LIST OF FIGURES

No.	Caption	Page
Fig. 2.1	Schematic Diagram of a Rotor-Shaft-Bearing System with an Electromagnetic Actuator	22
Fig. 2.2	Geometry of the Stator and the Arrangements of Coils and Poles for the Electromagnetic Actuator	23
Fig. 2.3	Schematic Diagram of a Magnetic Circuit Formed between the Rotor-Shaft and the Stator-Pole	24
Fig. 2.4	Block Diagram Representation of the Control Strategy Adopted by the Electromagnetic Actuator	30
Fig. 2.5	Comparison of Controlled and Uncontrolled UBR of Disc-2	42
Fig. 2.6	Comparison of Controlled and Uncontrolled UBR of Disc-1	43
Fig. 2.7	Comparison of Controlled and Uncontrolled UBR of Disc-3	43
Fig. 2.8	Campbell Diagram for First Two Pairs (Forward and Backward) of Natural Modes for the Uncontrolled Rotor	44
Fig. 2.9	Campbell Diagram for First Two Pairs (Forward and Backward) of Natural Modes for the Controlled Rotor	44
Fig. 2.10	Variation of Damping Ratio for First Six Modes for the Uncontrolled Rotor	45
Fig. 2.11	Variation of Damping Ratio for First Six Modes for the Controlled Rotor	46
Fig. 2.12	Variation of UBR at Node 6 of the Rotor with Different N and Same A_p	47
Fig. 2.13	Variation of UBR at Node 6 of the Rotor with Different A_p and Same N	47
Fig. 2.14	Influence of N on Control Current	49
Fig. 2.15	Influence of A_p on Control Current	49
Fig. 2.16	GPUBR of the Uncontrolled and Controlled Rotor	51
Fig. 2.17	Stability Margin of the Rotor with and without Control Action	52
Fig. 2.18	Variation of I_{cY} and I_{cZ} for Different Actuator Locations	52

Fig. 2.19	Variation of Forces at the Left Bearing for Uncontrolled and Controlled Rotor	53
Fig. 2.20	Variation of Forces at the Right Bearing for Uncontrolled and Controlled Rotor	53
Fig. 3.1	Rotor-Bearing System on Moving Base with Different Co-Ordinate Systems	58
Fig. 3.2	Transformation of the Orientation from the Frame F_0 to the Frame F_b in terms of three Successive Euler Angles	59
Fig. 3.3	Zones of Instability in the Parameter of Excitation due to the Harmonic Pitching Motion	74
Fig. 3.4	Campbell Diagram for the Uncontrolled Rotor-Shaft Bearing System on the Stationary Base	76
Fig. 3.5	Uncontrolled Response at the Mid-Point of the Rotor-Shaft System at 2400 rpm with a Base Excitation due to Pitching Motion of an Amplitude 0.3 rad and a Frequency 185 rad/s	77
Fig. 3.6	Controlled Response at the Mid-Point of the Rotor-Shaft System at 2400 rpm with a Base Excitation due to Pitching Motion of an Amplitude 0.3 rad and a Frequency 185 rad/s	78
Fig. 3.7	Control Current Variation for Controlled Response of the Rotor-Shaft System at 2400 rpm, with a Base Excitation due to Pitching Motion of an Amplitude 0.3 rad and a Frequency 185 rad/s	78
Fig. 3.8	Uncontrolled Response at the Mid-Point of the Rotor-Shaft System at 3000 rpm, with a Base Excitation due to Pitching Motion of an Amplitude 0.3 rad and a Frequency 200 rad/s	79
Fig. 3.9	Controlled Response at the Mid-Point of the Rotor-Shaft System at 3000 rpm, with a Base Excitation due to Pitching Motion of an Amplitude 0.3 rad and a Frequency 200 rad/s	80
Fig. 3.10	Control Current Variation for Controlled Response of the Rotor-Shaft System at 3000 rpm, with a Base Excitation due to Pitching Motion of an Amplitude 0.3 rad and a Frequency 200 rad/s	80
Fig. 3.11	Uncontrolled Response during Negotiating a Turn with the Rotor Spinning at 2000 rpm	83
Fig. 3.12	Controlled Response during Negotiating a Turn with the Rotor Spinning at 2000 rpm	83
Fig. 3.13	Effect of Aircraft Forward Speed on Uncontrolled Response during Negotiating a Turn with the Rotor Spinning at 2000 rpm	84

Fig. 3.14	Effect of Aircraft Forward Speed on Controlled Response during Negotiating a Turn with the Rotor Spinning at 2000 rpm	84
Fig. 3.15	Uncontrolled Response during Negotiating a Turn with the Rotor Spinning at 5000 rpm (with Internal Damping)	85
Fig. 3.16	Controlled Response during Negotiating a Turn with the Rotor Spinning at 5000 rpm (with Internal Damping)	86
Fig. 3.17	Temporal Variation of Control Current during Negotiating a Turn with the Rotor spinning at 5000 rpm (with Internal Damping)	86
Fig. 3.18	Uncontrolled Response during Diving in a Sine Curve with the Rotor Spinning at 2000 rpm	88
Fig. 3.19	Controlled Response during Diving in a Sine Curve with the Rotor Spinning at 2000 rpm	89
Fig. 3.20	Effect of Depth of Dive on the Uncontrolled Response	90
Fig. 3.21	Effect of Depth of Dive on the Controlled Response	90
Fig. 4.1	Schematic Diagram of the Rotor-Shaft-Bearing System with Electromagnetic Actuator	94
Fig. 4.2	Rotor Disc with Mass-Unbalance and the Sets of Stationery and Rotating Axes	94
Fig. 4.3	Variation of Maximum Radius of Rotor Orbit vs. Spin Speed (Within 10 s of Rotor-Operation)	113
Fig. 4.4	Temporal Variation of the Uncontrolled Response Components of the Rotor at 540 rpm (Without External Torque)	114
Fig. 4.5	Temporal Variation of the Uncontrolled Response Components of the Rotor at 900 rpm (Without External Torque)	114
Fig. 4.6	FFT of the Uncontrolled Response Components of the Rotor at 540 rpm (Without External Torque)	115
Fig. 4.7	FFT of the Uncontrolled Response Components of the Rotor at 900 rpm (Without External Torque)	116
Fig. 4.8	Temporal Variation of the Controlled Response Components of the Rotor at 540 rpm (Without External Torque)	117
Fig. 4.9	Temporal Variation of the Control Current Components at 540 rpm (Without External Torque)	118

Fig. 4.10	Temporal Variation of the Controlled Response Components of the Rotor at 900 rpm without external torque	118
Fig. 4.11	Temporal Variation of the Control Current Components at 900 rpm (Without External Torque)	119
Fig. 4.12	FFT of the Controlled Response Components of the Rotor at 540 rpm (Without External Torque)	120
Fig. 4.13	FFT of the Controlled Response Components of the Rotor at 900 rpm (Without External Torque)	120
Fig. 4.14	Temporal Variation of the Uncontrolled Response Components of the Rotor at 900 rpm (With 100 N·m External Torque)	121
Fig. 4.15	Temporal Variation of the Controlled Response Components of the Rotor at 900 rpm (With 100 N·m External Torque)	122
Fig. 4.16	Temporal Variation of the Control Current Components at 900 rpm (With 100 N·m External Torque)	122
Fig. 4.17	FFT of the Uncontrolled Response Components of the Rotor at 900 rpm (With 100 N·m External Torque)	123
Fig. 4.18	FFT of the controlled response components of the rotor at 900 rpm (With 100 N·m External Torque)	124
Fig. 5.1	Finite Element Model of the Rotor-Bearing System	133
Fig. 5.2	Comparison between UBR at Node 6 of the Full Model and the Reduced Model without Internal Damping	135
Fig. 5.3	Campbell Diagram Showing the Variations of the Six Lowest Eigenfrequencies of Full Model without Internal Damping	135
Fig. 5.4	Campbell Diagram Showing the Variations of Eigenfrequencies of the Reduced Model Formed with First Two Natural Modes, without Internal Damping	136
Fig. 5.5	Campbell Diagram Showing Variations of First Six Eigenfrequencies of the Reduced Model Formed with First Eight Natural Modes, without Internal Damping	136
Fig. 5.6	Comparison of the Real Parts of the Frequency Response at node 6 along Y_0 -direction at 3500 rpm for Different Number of Modes, without Internal Damping	139
Fig. 5.7	Comparison of the Imaginary Parts of the Frequency Response at node 6 along Y_0 -direction at 3500 rpm for Different Number of Modes, without Internal Damping	140

Fig. 5.8	Comparison of the Real Parts of the Frequency Response at node 6 along Z_0 -direction at 3500 rpm for Different Number of Modes, without Internal Damping	140
Fig. 5.9	Comparison of the Imaginary Parts of the Frequency Response at node 6 along Z_0 -direction at 3500 rpm for Different Number of Modes, without Internal Damping	141
Fig. 5.10	Comparison of UBR at Node 6 of the Rotor, with Internal Damping	142
Fig. 5.11	Comparison of the Real Parts of the Frequency Response at node 6 along Y_0 -direction at 3500 rpm for Different Number of Modes, with Internal Damping	143
Fig. 5.12	Comparison of the Imaginary Parts of the Frequency Response at node 6 along Y_0 -direction at 3500 rpm for Different Number of Modes, with Internal Damping	143
Fig. 5.13	Comparison of the Real Parts of the Frequency Response at node 6 along Z_0 -direction at 3500 rpm for Different Number of Modes, with Internal Damping	144
Fig. 5.14	Comparison of the Imaginary Parts of the Frequency Response at node 6 along Z_0 -direction at 3500 rpm for Different Number of Modes, with Internal Damping	144
Fig. A.1	Change of Orientation of the Disc in Terms of Euler Angles	158
Fig. A.2	Different Sets of Axes Used to Represent the Shaft Deformation and Rotation due to Bending and Spinning	160
Fig. A.3	Projection of the Differential Portion of the Rotor-Shaft in $X-\zeta$ Plane	161

LIST OF TABLES

No.	Caption	Page
Table 2.1	Parameters of the Rotor-Shaft	41
Table 2.2	Details of the Discs	41
Table 2.3	Values of k_{mag} for Different Combination of A_p and N	48
Table 2.4	Influence of Actuator and Its Location on GPUBR	50
Table 3.1	Parameters of the Rotor-Shaft System	75
Table 3.2	Actuator and Controller Parameters for Example 1	77
Table 3.3	Actuator and Controller Parameters	81
Table 4.1	Geometry and Other Properties of the Rotor-Shaft and the Disc	112
Table 4.2	Actuator and Control Parameters	117
Table 5.1	Comparison between Original and Predicted Modes at 3500 rpm	137
Table 5.2	Comparison between Original and Predicted Modes at 3800 rpm	138
Table 5.3	Comparison between Original and Predicted Modes at 15000 rpm	138