CONTENTS

| | Page No. |
|---|----------|
| Title Page | i |
| Certificate by the Supervisor | iii |
| Declaration | iv |
| Acknowledgement | V |
| Contents | vi-xi |
| List of Symbols | xii-xiii |
| Abstract | xiv |
| Chapter 1 Introduction and Objectives | 1-26 |
| 1.1 Introduction | 1-8 |
| 1.1.1 Arsenic chemistry | 2-4 |
| 1.1.2 Occurrence and mobilization of arsenic in groundwater | 4-6 |
| 1.1.3 Health hazards of arsenic | 6-8 |
| 1.1.4 Social impact of arsenicosis | 8 |
| 1.2 Arsenic removal technologies | 8-19 |
| 1.2.1 Oxidation | 10 |
| 1.2.2 Chemical coagulation-precipitation and electrocoagulation | 11 |
| 1.2.3 Ion Exchange | 11 |
| 1.2.4 Membrane Technology | 12 |
| 1.2.5 Adsorption | 12-20 |
| 1.3 Laterite and treated laterite used as adsorbent in this study | 20-22 |
| 1.4 Approaches to improve performances of adsorbent | 22-24 |
| 1.5 Organization of experimental work | 24-25 |
| 1.6 Aim/Objective of the current research | 25-26 |
| 1.7 Organization of the thesis | 26 |
| Chapter 2 Application of raw laterite as arsenic adsorbent | 27-94 |
| 2.1 Introduction | 27-28 |
| 2.2 Experimental | 28-36 |

| | 2.2.1 Arsenic spiked water | 28-29 |
|-----|---|-------|
| | 2.2.2 Arsenic contaminated groundwater | 29 |
| | 2.2.3 Preparation of Adsorbent (Raw laterite) | 29 |
| | 2.2.4 Experimental Procedure | 29-31 |
| | 2.2.5 Conduction of adsorption experiments | 31-32 |
| | 2.2.6 Conduction of desorption experiments | 32-33 |
| | 2.2.7 Conduction of leaching study of KRL | 33-34 |
| | 2.2.7.1 Toxicity Characteristic Leaching Procedure (TCLP) | 33-34 |
| | 2.2.7.2 Synthetic landfill leachate (SSL) | 34 |
| | 2.2.8 Analysis | 34-36 |
| | 2.2.8.1 Adsorbent characteristics | 34-35 |
| | 2.2.8.2 Arsenic measurement | 35-36 |
| 2.3 | Results and discussions | 36-94 |
| | 2.3.1 Adsorbent characteristics | 36-42 |
| | 2.3.2 Isotherm study of As(III) and As(V) on RL | 42-55 |
| | 2.3.2.1 Selection of the operating conditions for the adsorption study of | 42-44 |
| | As(V) and As(III) using KRL as adsorbent | |
| | 2.3.2.2 Effect of pH of the solution | 44-46 |
| | 2.3.2.3 Equilibrium studies | 46-55 |
| | 2.3.2.3.1 Arsenic adsorption isotherm on different RL samples | 47-48 |
| | 2.3.2.3.2 As(III) adsorption isotherm using RL adsorbent | 48-52 |
| | 2.3.2.3.3 As(V) adsorption isotherm | 52-54 |
| | 2.3.2.3.4 Arsenic adsorption isotherm using contaminated | 54-55 |
| | groundwater (CGW)/RL system | |
| | 2.3.3 Kinetic study | 56-62 |
| | 2.3.3.1 As(III) adsorption kinetics | 56-59 |
| | 2.3.3.1.1 Order of adsorption kinetics of As(III) | 57 |
| | 2.3.3.1.2 Effect of Initial As(III) concentration | 58 |
| | 2.3.3.1.3 Effect of adsorbent dose on As(III) adsorption in the | 58-59 |
| | kinetic study | |
| | 2.3.3.2 As(V) adsorption kinetics | 59-62 |

| 2.3.3.2.1 Effect of the initial As(V) concentration | 59-61 |
|---|-------|
| 2.3.3.2.2 Effect of ionic strength on adsorption kinetic | 61-62 |
| 2.3.3.2.3 Effect of Temperature on Adsorption Kinetics | 62 |
| 2.3.4 Competitive ions effect on As(III)/As(V) adsorption | 62-60 |
| 2.3.4.1 Anionic interference on As(III)/As(V) adsorption | 62-64 |
| 2.3.4.2 Cationic interference on As(III)/As(V) ions adsorption | 65 |
| 2.3.4.3 Mixed ions interference on As(III)/As(V) ions adsorption | 65-66 |
| 2.3.5 Modeling of adsorption kinetics | 67-77 |
| 2.3.5.1 Theory | 67-70 |
| 2.3.5.2 Numerical Method | 70-71 |
| 2.3.5.3 Experimental conditions for kinetic modeling | 71 |
| $2.3.5.4$ Estimated values of D_e and K_f | 71 |
| 2.3.5.5 Parametric study | 72-76 |
| 2.3.5.5.1 Effect of initial adsorbate concentration | 72-74 |
| 2.3.5.5.2 Effect of temperature | 75 |
| 2.3.5.5.3 Effect of Biot number | 75 |
| 2.3.5.5.4 Effect of the mass of adsorbent to the solution volume | 75-76 |
| 2.3.5.6 Arsenic adsorption kinetics of arsenic CGW on RL | 77 |
| 2.3.6 Fixed-bed adsorption of As(III) and As(V) on RL | 78-87 |
| 2.3.6.1 Mathematical analysis of fixed-bed experimental data | 78-79 |
| 2.3.6.2 Adams-Bohart model | 79-8 |
| 2.3.6.3 Design of adsorption column by the BDST model | 81-82 |
| 2.3.6.4 Design of adsorption column for different inlet concentration | 82-83 |
| 2.3.6.5 Design of adsorption column for different flow rate | 83 |
| 2.3.6.6 Effect of the bed depth of the column | 83 |
| 2.3.6.7 Effect of interruption of operation | 83-85 |
| 2.3.6.8 Effect of inlet As(V) concentration | 85-86 |
| 2.3.6.9 Quality of effluent water | 87 |
| 2.3.7 Fixed-bed adsorption of arsenic on RL using CGW | 87-88 |
| 2.3.8 Pressure drop develop in fixed-bed column | 88 |
| 2.3.9 Desorption/leaching study of arsenic-loaded RL | 89-93 |

| 2.3.9.1 Desorption study using alkali solution | 89-90 |
|---|---------|
| 2.3.9.2 Recycling of used adsorbent | 91 |
| 2.3.9.3 Leaching study | 91-93 |
| 2.3.9.3.1 Leaching effect of pH of solution on RL | 91-92 |
| 2.3.9.3.2 Toxicity Characteristic Leaching Procedure (TCLP) | 92 |
| 2.4 Conclusion | 93-94 |
| Chapter 3 Application of acid treated laterite as arsenic adsorbent | 95-118 |
| 3.1 Introduction | 95-96 |
| 3.2 Experimental and Method | 96-99 |
| 3.2.1 Materials | 96-97 |
| 3.2.1.1 Preparation of acid activated laterite | 96-97 |
| 3.2.2 Experiment | 97-99 |
| 3.2.2.1 Equilibrium study | 97-98 |
| 3.2.2.2 Kinetic study | 98 |
| 3.2.2.3 Fixed-bed study | 98 |
| 3.2.2.4 Conduction of desorption experiments | 98 |
| 3.2.2.5 Leaching study of AAL (0.2 N) and arsenic-loaded AAL(0.2 N) |) 98-99 |
| 3.2.3 Analysis | 99 |
| 3.3 Results and discussion | 99-118 |
| 3.3.1 Adsorbent characterization | 99-104 |
| 3.3.2 Selection of acid concentration in acid activation step | 104-105 |
| 3.3.3 Equilibrium studies | 105-108 |
| 3.3.3.1 Arsenic adsorption using As(V)/As(III) spiked water | 105-107 |
| 3.3.3.2 Arsenic adsorption using CGW | 107-108 |
| 3.3.4 Kinetic study | 108-112 |
| 3.3.4.1 Kinetic model | 108-109 |
| 3.3.4.2 Effect of initial arsenic concentration | 109 |
| 3.3.4.3 Effect of temperature | 109-110 |
| 3.3.4.4 Effect of particle size | 111 |
| 3.3.4.5 Adsorption kinetics using CGW | 111-112 |

| 3.3.5 Competitive ions effect on As(III)/As(V) ions adsorption | 112-114 |
|---|---------|
| 3.3.5.1 Anionic interference on As(III)/As(V) ions adsorption | 112-113 |
| 3.3.5.2 Cationic interference on As(III)/As(V) ions adsorption | 113-114 |
| 3.3.6 Fixed-bed adsorption of arsenic | 114-117 |
| 3.3.6.1 Regeneration of arsenic-loaded fixed-bed column and | 117 |
| reuse for adsorption | |
| 3.3.7 Leaching study of fresh AAL(0.2 N) and arsenic | 117-118 |
| adsorbed AAL(0.2 N) | |
| 3.3.7.1 Leaching effect of pH of solution on AAL(0.2 N) | 117-118 |
| 3.4 Conclusion | 118 |
| Chapter 4 Application of TL as arsenic adsorbent | 119-170 |
| 4.1 Introduction | 119-120 |
| 4.2 Experimental and Method | 120-126 |
| 4.2.1 Materials | 120-122 |
| 4.2.1.1 Preparation of acid-base treated laterite | 121-122 |
| 4.2.2 Experiment | 122-125 |
| 4.2.2.1 Equilibrium study | 122-123 |
| 4.2.2.2 Fixed-bed study | 123-124 |
| 4.2.2.3 Household column filter design | 124 |
| 4.2.2.4 Conduction of desorption experiments | 124-125 |
| 4.2.2.5 Leaching study of TL and arsenic-loaded TL | 125 |
| 4.2.3 Analysis | 126 |
| 4.3 Results and discussion | 127-169 |
| 4.3.1 Optimization of treatment conditions | 127-128 |
| 4.3.2 Adsorbent characterization | 128-142 |
| 4.3.2.1 Characterization of KTL | 128-139 |
| 4.3.2.2 Characterization of KTL, BTL, PTL1, and PTL2 | 139-142 |
| treated at optimal condition | |
| 4.3.3 Batch mode arsenic adsorption on treated laterite | 142-169 |
| 4.3.3.1 Effect of treatment parameters on arsenic adsorption isotherm | 142-144 |

| Appendix A | | 193-195 |
|---------------|---|---------|
| References | | 179-191 |
| Chapter 5 | Conclusions and perspective of future work | 177-178 |
| 4.4 Conclusio | ns | 175-176 |
| | 4.3.3.10.1 Leaching effect of pH of solution on TL | 174 |
| 4.3.3 | 3.10 Leaching study of fresh TL arsenic adsorbed TL | 174-175 |
| | 4.3.3.9.6 Household filter performance | 173-174 |
| | 4.3.3.9.5 Pressure drop develop in fixed-bed column | 172-173 |
| | TL and activated alumina bed using CGW | |
| | 4.3.3.9.4 Comparison of fixed-bed column performance between | 171-172 |
| | 4.3.3.9.3 Regeneration and reuse of TL fixed-bed in column run | 171 |
| | breakthrough behavior | |
| | 4.3.3.9.2.2 Thomas and W-J model predicted | 167-171 |
| | modeling | |
| | 4.3.3.9.2.1 Thomas and Wheeler-Jonas fixed-bed | 165-167 |
| | 4.3.3.9.2 Fixed-bed modeling | 162-171 |
| | spiked distilled water and CGW | |
| | 4.3.3.9.1 Fixed-bed column study using As(V) and As(III) | 159-162 |
| | 3.9 Fixed-bed column study | 159-174 |
| 4.3.3 | 8.8 Effect of other ions on As(III) and As(V) adsorption | 158-159 |
| | arsenic species | 130-137 |
| | 4.3.3.7.2 Shrinking core model applied to system containing both | |
| 4.3.3 | 3.7 Kinetic modeling of TL/arsenic system 4.3.3.7.1 Estimated values of D _e and K _f for single arsenic system | 155-157 |
| | 3.6 Effect of treatment parameters on arsenic adsorption kinetics | 153-155 |
| | 3.5 Effect of pH on adsorption isotherm | 150-152 |
| | adsorbent KTL, BTL, PTL1, and PTL2 | |
| 4.3.3 | 3.4 Comparison of arsenic adsorption performance using | 149-150 |
| 4.3.3 | 3.3 Isotherm of binary adsorbate system | 148-149 |
| 4.3.3 | 3.2 Comparison of adsorption capacity of TL with other adsorbents | 144-147 |

| Appendix B | 195 |
|------------------|---------|
| Curriculum Vitae | 197-198 |

