

CONTENTS

| | |
|---|-----------|
| Title page | i |
| Certificate of approval of the viva-voce board | iii |
| Certificate by the supervisors | v |
| Dedication | vii |
| Acknowledgements | ix |
| Declaration | xi |
| Curriculum vitae | xiii |
| Contents | xv |
| List of figures | xix |
| List of tables | xxiii |
| Nomenclature | xxv |
| Abstract | xxix |
| Chapter 1: Introduction | 1 |
| 1.1. Understanding natural circulation | 1 |
| 1.2. NCL in nuclear applications | 3 |
| 1.3. Different configurations of NCL | 4 |
| 1.4. Brief overview of available literature | 6 |
| 1.4.1. Concept of natural circulation and flow instability | 7 |
| 1.4.2. Natural circulation in solar thermal systems | 10 |
| 1.4.3. Investigations on Toroidal NCLs | 11 |
| 1.4.4. Transformation towards rectangular geometry | 14 |
| 1.4.5. Stability issues related to rectangular NCL | 19 |
| 1.4.6. Studies on different alternative loop configurations | 23 |
| 1.4.7. Instability in two-phase NCLs | 26 |
| 1.4.8. Entrainment in two-phase NCLs with phase separation | 30 |
| 1.5. Motivation of the present thesis | 32 |
| 1.6. Organization of the thesis | 34 |
| Chapter 2: Generalized Analysis of Single-phase Natural Circulation Loop | 37 |
| 2.1. Background with Single-phase NCLs | 37 |
| 2.2. Development of generalized model | 39 |
| 2.2.1. Physical description and simplifying assumptions | 39 |
| 2.2.2. Governing equations | 40 |
| 2.2.3. Non-dimensionalization of governing equations | 41 |
| 2.2.4. Steady-state solutions | 43 |
| 2.2.5. Numerical solution procedure | 52 |
| 2.2.6. Transient analysis | 53 |
| 2.2.7. Thermodynamic property estimation | 54 |
| 2.3. Some thoughts on different selections | 54 |
| 2.3.1. Choice of reference temperature (T_0) | 55 |
| 2.3.2. Estimation of average thermal expansion coefficient (β_{av}) | 55 |
| 2.3.3. Selection of friction factor (f_{av}) correlations | 56 |
| 2.3.4. Selection of heat transfer relations | 56 |
| 2.3.5. Influence of vertical length scale (L_v) | 58 |
| 2.4. Model validation with experimental results | 58 |

| | |
|---|------------|
| 2.5. Transient response of rectangular NCL | 61 |
| 2.6. Comparison of rectangular and toroidal geometries | 66 |
| 2.7. Epilogue | 71 |
| Chapter 3: Stability Control and Dynamic Performance of a Single-phase Rectangular NCL | 73 |
| 3.1. Preamble | 73 |
| 3.2. Effect of Geometric Parameters | 75 |
| 3.2.1. Effect of inner diameter (d_i) | 76 |
| 3.2.2. Effect of loop height (L_v) | 78 |
| 3.2.3. Effect of heater length (L_h) | 80 |
| 3.2.4. Effect of the length of insulated horizontal section | 81 |
| 3.2.5. A general stability relation | 81 |
| 3.3. Influence of Additional Resistances | 82 |
| 3.4. Influence of Loop Inclination | 84 |
| 3.5. Dynamic Performance of NCL | 87 |
| 3.6. Epilogue | 92 |
| Chapter 4: Analysis of Single-phase Rectangular NCL as a Conjugate Problem with Ambient Heat Leakage | 95 |
| 4.1. Requirement of quantitative prediction | 95 |
| 4.2. Mathematical modeling | 97 |
| 4.2.1. Governing equations | 98 |
| 4.2.2. Non-dimensionalization of governing equations | 100 |
| 4.2.3. Heat transfer and friction factor relations | 101 |
| 4.2.4. Solution procedure | 102 |
| 4.3. Results and discussion | 103 |
| 4.3.1. Model validation with experimental data | 103 |
| 4.3.2. General temperature profiles | 103 |
| 4.3.3. Effect of ambient | 105 |
| 4.3.4. Effect of inner diameter (d_i) | 111 |
| 4.3.5. Effect of loop height (L_v) | 114 |
| 4.3.6. Effect of horizontal length | 118 |
| 4.3.7. Effect of heater length (L_h) | 120 |
| 4.3.8. Effect of wall thickness ($(d_o - d_i)/2$) | 123 |
| 4.3.9. Effect of coolant parameters | 124 |
| 4.3.10. Effect of wall insulation | 126 |
| 4.4. Epilogue | 128 |
| Chapter 5: Analysis of Two-phase Rectangular NCL with Thermodynamic Non-equilibrium | 131 |
| 5.1. Preamble | 131 |
| 5.2. Modelling of subcooled boiling | 132 |
| 5.3. Theoretical formulation | 135 |
| 5.3.1. Modelling assumptions | 135 |
| 5.3.2. Boiler section | 136 |
| 5.3.2.1. Single-phase liquid region | 136 |
| 5.3.2.2. Subcooled boiling region | 136 |
| 5.3.2.3. Saturated boiling region | 138 |
| 5.3.3. Riser section | 138 |

| | |
|--|-----|
| 5.3.4. Condenser section | 139 |
| 5.3.5. Pressure drop around the loop | 140 |
| 5.4. Results and discussion | 140 |
| 5.4.1. Typical loop flow rate characteristics | 141 |
| 5.4.2. Comparison with boiling channel data | 146 |
| 5.4.3. Generalized working regime map | 146 |
| 5.4.4. Influence of sink condition | 150 |
| 5.4.5. Influence of loop height | 155 |
| 5.4.6. Influence of loop diameter | 157 |
| 5.4.7. Influence of the length of heat-exchanging sections | 158 |
| 5.5. Epilogue | 160 |
| Chapter 6: Experimental Investigations of Carryover and Carryunder Phenomena in a Simulated AHWR Loop | 163 |
| 6.1. Preamble | 163 |
| 6.2. Design of experimental facility | 164 |
| 6.2.1. Important design decisions | 165 |
| 6.2.2. Scale-down analysis of NCL | 165 |
| 6.2.3. Entrainment analysis | 169 |
| 6.2.4. Annular flow at riser outlet | 170 |
| 6.3. Details of experimental facility | 171 |
| 6.4. Experimental observations | 174 |
| 6.4.1. Probe signal analysis | 175 |
| 6.4.2. Natural circulation behaviour | 178 |
| 6.4.3. Carryover measurement | 179 |
| 6.4.4. Use of screens to suppress carryover | 183 |
| 6.4.5. Carryunder identification | 189 |
| 6.5. Epilogue | 190 |
| Chapter 7: Conclusions and Scope for Future Study | 193 |
| 7.1. Conclusions | 193 |
| 7.1.1. Unified model for single-phase NCLs | 193 |
| 7.1.2. Stability control for single-phase NCLs | 194 |
| 7.1.3. Rectangular NCL with heat leakage to the ambient | 195 |
| 7.1.4. Two-phase NCL with thermal non-equilibrium | 196 |
| 7.1.5. Experimental investigations of carryover and carryunder | 197 |
| 7.2. Scope for future study | 198 |
| References | 201 |
| List of Publications | 219 |